

AQUATOP®

Polyester Marine Fabric

ROLL SIZE

65 yards

BACK COATING

Polyurethane

APPLICATION

Marine

SCRIM COUNT

600D

FIBER TYPE

Polyester

BAG TEST

8+24 hour pass

WEIGHT

8.75 oz/yd²

SUBSTRATE FABRIC TYPE

Polyester

WIDTH

60"

GRAB TENSILE

450x350

HEAT SEALABLE

Yes w/tape

HYDROSTATIC

80+

MILDEW RESISTANCE

Yes

SPRAY RATING

100

TENSILE STRENGTH

420x330

TONGUE TEAR

22x20

UV RESISTANCE

Yes

WATER REPELLENCY

Yes

WARRANTY INFO

Aquatop® coated polyester fabric, when used properly, is guaranteed for a period of five (5) years from date of original installation against excessive loss of color or strength from normal exposure conditions, including sunlight, rot, or normal atmospheric chemicals which might render it unserviceable.

In the unlikely event of fabric failure during the five year period, Rochford Supply will at its option, supply the original purchaser of the fabric either replacement fabric or credit of the original fabric value. This warranty does not cover labor, installation, or fabrication costs.

This warranty protects you against damage to covers used under normal conditions. It does not cover damage from Acts of God, vandalism, neglect or use or care not in accordance with Rochford Supply's use and care instructions.

This warranty is in lieu of all warranties expressed or implied and Rochford Supply will not be liable for any consequential or incidental damage. Any implied warranties imposed by law are limited in time to the duration of the expressed warranty.

CARE AND CLEANING**Aquatop® Care**

Aquatop® fabric is finished to resist the growth of mildew. However, it should not be folded and stored while wet. Accumulations of dirt and animal droppings which can support growth of mildew and result in fabric staining, should be removed periodically by recommended cleaning methods.

The pigmentation in Aquatop® fabric will not migrate onto upholstery vinyl. If some surface rub-off should occur it can easily be removed with vinyl cleaner or mineral spirits. In areas where vigorous movement of the fabric against a hard surface will occur during use, use of a buffer strip is recommended.

Aquatop® Cleaning

Aquatop® fabric may be cleaned with a cleaning solution of 4 ounces of bleach and 2 ounces of mild soap mixed in one gallon of warm (100 F) water. Do NOT use detergents. Use a soft, bristled brush to lift soil embedded in the fabric surface. Rinse thoroughly with clear water to remove soil and soap residue. After thorough cleaning and drying, water repellency may be reduced.



SCAN HERE



7624 Boone Ave. N, Suite 200, Brooklyn Park, MN 55428
(763) 447-6600 • TOLL FREE (800) 334-6414
www.rochfordsupply.com • Email: info@rochfordsupply.com